

Flow & Level Instruments



GREYLINE
instruments inc.

www.greyline.com
RELIABLE MEASUREMENT & CONTROL

Level with Non-Contacting Ultrasonic Sensors

- Monitors Level or Open Channel Flow
- Displays and Totalizes
- Isolated 4-20mA
- False Echo Rejection
- 2 Programmable Control Relays
- Intrinsically Safe Sensor Option



New! SLT 5.0 Level & Flow Monitor

Use this powerful new instrument to continuously measure, display, transmit and control level in tanks and pumping stations, or to monitor and totalize Open Channel flow through any flume or weir. Features a user-friendly keypad calibration system, backlit LCD display, an isolated 4-20mA output and a watertight electronics enclosure. Includes a non-contacting ultrasonic sensor which is rated Intrinsically Safe with optional safety barrier, and built-in temperature compensation for high accuracy. Plug-and-Play options include extra control relays and a 2-million point data logger.

- Non-Contacting Ultrasonic Sensor
- 6 Control Relays
- Programmable Pump Alternation
- RS232 and PC Software
- Relay 'Run Time' Reports
- Isolated 4-20mA Output



PSL Pump Station Level Controller

Designed for pump stations, wet wells and tank level control. The Greyline PSL includes 6 control relays for pump control (with programmable alternation), level alarms, dialers, or fault alarms. Features a non-contacting, ultrasonic sensor, large 4-digit display, isolated 4-20mA and RS232 outputs. The PSL automatically stores relay run time reports for pump performance analysis. Calibrate with the built-in keypad, or with password-protected "PSL Remote" Windows™ software – Free with each PSL. Use "PSL Remote" and modems to dial-up Pump Stations and monitor wet-well level and relay states from your PC.

- Two Non-Contacting Ultrasonic Sensors
- Differential Level Control plus Open Channel Flow
- User-friendly Calibration system
- Intrinsically Safe Sensor Option



New! DLT 2.0 Differential Level Transmitter

A simple solution for barscreen level control at wastewater treatment plant headworks, pump stations and combined sewer systems. Install one Sensor on each side of a mechanical barscreen to continuously monitor, transmit and control level. Use the built-in control relays or 4-20mA outputs to automatically activate the barscreen rake at preset levels. The downstream sensor can also be installed above a flume to measure and totalize open channel flow. Intrinsically safe sensors and built-in data logger are optional.

- Low Cost
- Isolated 4-20mA Output
- Large LCD Display
- Programmable Signal Relay
- Non-Contacting Sensor
- Watertight Enclosure
- Built-in Keypad Calibrator



LIT25 Level Indicating Transmitter

This compact Transmitter displays, controls and transmits level. Mount the non-contacting ultrasonic sensor at the top of your tank, and the compact, watertight electronics/display enclosure at a convenient location nearby. Use the built-in signal relay or isolated 4-20mA to transmit level to a PLC, and the Display as a local indicator. Features a simple, built-in menu/calibration system, temperature compensation, and self-tunes to extended sensor cable lengths. LIT25 - the ideal indicating, controlling smart level transmitter for tank level systems.

- Non-Contacting Ultrasonic
- Optional Measurement Ranges
- Optional Cable Lengths
- Models for Chemical Compatibility and Intrinsic Safety



Ultrasonic Level Sensors

Each instrument includes a standard ultrasonic sensor, or you can choose from a wide range of optional models for chemical compatibility, measurement range, mounting configuration and intrinsic safety. Ultrasonic sensors are non-contacting and there are no moving parts. They are installed above the liquid being measured. Greyline sensors auto-tune to the cable length. Cables can be field-extended with a junction box for sensor installation up to 500 ft (152 m) from the instrument electronics.

Flow Sensors Strap-On the Outside of a Pipe

- Strap-on Sensor
- Backlit LCD Display
- 18-Digit Totalizer
- Isolated 4-20mA Output
- Watertight Enclosure
- Built-in 5-Key Calibrator
- RFI Rejection Filters
- Signal Strength Display
- 2 Control Relays



DFM 5.0 Doppler Flow Meter

Continuously monitor flow from outside a pipe. Includes an isolated 4-20mA output and 2 programmable control relays. Ideal for wastewater, chemicals, viscous liquids and slurries. No obstruction and no contact with the moving liquid. The standard sensor mounts on any pipe over 1/2" (12.7 mm) ID. The large, backlit LCD displays and totalizes bi-directional flow in gallons, liters, or any unit of measure. Shielded sensor cable self-tunes to extended lengths. Options include built-in data logger with direct output to USB Flash drives.

- For Dirty Liquids
- Strap-on Sensor
- Battery Powered
- Built-in 5-Key Calibrator
- Programmable Totalizer
- Fast, Easy Operation
- 4-20mA Output
- Data Logger, USB Output and PC Software



New! PDFM 5.0 Portable Doppler Flow Meter

Ideal for flow troubleshooting, balancing and checking permanent flow meters. Mount the PDFM 5.0 sensor on the outside of a pipe to transmit, display and totalize flow in gallons, liters or any other unit of measure. It takes just a few seconds to install and calibrate. AC/DC powered with built-in rechargeable battery. The standard sensor fits any pipe ID from 1/2" to 180" (12.5 mm to 4.5 m). Includes 4-20mA output, programmable totalizer, adjustable sensitivity and damping. Built-in 300,000 point data logger with PC software and USB output for transfers to a computer.

- For Clean Liquids
- Wide Range of Pipe Sizes
- Battery Powered
- Measures and Totalizes Flow in Both Directions
- 4-20mA Output
- Pulse Output
- Data Logger and USB Output



New! PT500 Portaflow Portable Transit Time Flow Meter

Deluxe model - Recommended for clean fluids like water, glycol, oil and most chemicals. Portaflow ultrasonic transducers mount on the outside of metal or plastic pipes. Transducers can be mounted without shutting down flow and there is no obstruction or pressure drop. Calibration is easy with the onscreen menu system and parameters for up to twenty different sites can be stored. The Portaflow totalizes and displays flow in both directions (as positive or negative flow rates). PT500 includes two transducer pairs for a wide range of pipe sizes, plus a built-in data logger with USB output.

- For Clean Liquids
- Select Range of Pipe Sizes
- Battery Powered
- Measures and Totalizes Flow in Both Directions
- 4-20mA Output
- Pulse Output



New! PT400 Portaflow Portable Transit Time Flow Meter

The PT400 model includes transducers for select pipe sizes. Measures flow of clean fluids with transducers clamped on the outside of plastic or metal pipes. The PT400 displays and totalizes flow in both directions (as positive or negative flow rates). Calibration is easy with the onscreen menu system and parameters for up to twenty different sites can be stored. Select either small pipe size or standard size transducers for your applications. Includes 4-20mA and programmable pulse outputs. Battery powered with external AC charger.

- Non-Contacting Sensor
- Easy Calibration
- Repeatable, Accurate
- 5 amp DPDT Relay
- Separate ON/OFF Set-point Adjustment
- Relay Status LED
- Adjustable Time Delay
- Intrinsic Safety Option



DFS-II Doppler Flow Switch

Control flow from outside a pipe. Recommended for liquids and pneumatically conveyed solids. Ideal for pump protection or to activate flow/no flow alarms. Sensor mounts on any pipe over 1 inch (25 mm) ID without shutting down flow. Includes one 5 amp DPDT control relay with adjustable time delay, and electronics housed in a watertight, dust tight enclosure. Includes bright LED indicators for relay status and signal strength. Installs in minutes and requires no maintenance. Accurate, repeatable - easy to install and calibrate.

Open Channel

Wastewater Flow Monitoring and Control

- Non-Contacting Sensor
- Built-in 2-million point Data Logger
- Daily Flow Reports
- Download to USB Flash Drives
- Isolated 4-20mA and 0-5V Outputs
- 2 Control Relays



New! OCF 5.0 Open Channel Flow Monitor

Monitor, display, totalize and datalog flow through any flume or weir. The automatic flow reporting system prepares and stores daily reports including total, minimum and maximum flow rates. It logs up to 2-million time and date stamped data points and downloads to USB Flash Drives. The OCF 5.0 includes isolated 4-20mA and 0-5V outputs. Two control relays are programmable for flow proportional pulse output and/or level alarm. Features a password protected keypad system for easy calibration. The non-contacting sensor is rated Intrinsically Safe with optional safety barrier. Temperature compensated for continuous high accuracy.

- Measures both Level and Velocity
- Displays and Totalizes
- Simple Calibration System
- 3 Isolated 4-20mA Outputs
- 2 Control Relays
- Watertight Enclosure



New! AVFM 5.0 Area-Velocity Flow Meter

Monitor flow through open channels of any shape, partially full sewer pipes and surcharged pipes *without* a flume or weir. Ideal for municipal stormwater, combined effluent, raw sewage and irrigation water. Uses a submerged ultrasonic sensor to continuously measure both Velocity and Level in the channel. Can be configured with the standard submerged Velocity/Level sensor, or with submerged velocity and a separate non-contacting ultrasonic level sensor. Intrinsically safe sensors, built-in data logger and pipe mounting bands are optional.

- Logs Level, Velocity and Temperature
- Operates up to 4 Years on Disposable Batteries
- 130,000 point Data Logger
- LCD Bargraph Display
- RS232 Output
- Watertight Enclosure



Stingray Portable Level-Velocity Logger

For flow surveys in open channels and partially filled pipes. The sealed ultrasonic sensor mounts on the bottom of the pipe or channel. Stingray operates on standard Alkaline D-cell batteries for up to four years! The built-in 130,000 point data logger stores water level, velocity and temperature readings at programmable intervals from 10 seconds to 20 minutes. Use Greyline Logger software (included) to monitor readings in real-time and to retrieve log files, calculate flow or export data to other spreadsheet or database programs. Stingray includes an LCD bargraph display and RS232 output.

- Built-into Instrument Electronics
- Includes USB or RS232 Outputs
- Powerful Software for Windows
- Store, Display, Graph and Export log files



Data Logging

Take the work out monitoring and reporting. Data Logger hardware is built into the instrument electronics and includes USB or RS232 outputs. The powerful 'Greyline Logger' software program runs in Windows to retrieve and display log files. Download directly to USB Flash Drives (available in most models) or connect your laptop to the instrument to download by RS232 or USB outputs. View data as graphics or tables. Save and export log files to other software programs for presentation and reporting.

How To Order

Contact a Greyline sales representative in your area or phone one of our sales engineers. Describe your requirements and receive our prompt quotation.

GREYLINE instruments inc.

Canada: 16456 Sixsmith Dr., Long Sault, Ont. K0C 1P0
Tel: 613-938-8956 / 888-473-9546 Fax: 613-938-4857
USA: 105 Water Street, Massena NY 13662
Tel: 315-788-9500 / 888-473-9546 Fax: 315-764-0419
Internet: www.greyline.com E-mail: info@greyline.com

RELIABLE MEASUREMENT AND CONTROL