

MOTOR ELECTRIC




SIEMENS ELECTRIC MOTOR TEFC 22KW/30HP/3PHASE/B5 - 2 POLE

Power : 22kw/30hp
Speed : 2pole/4pole/6pole
Voltage : 3phase
Mounting : B5
Class : F/IP55
Model : TEFC

SIEMENS

BEARING



SKF

Inside Diameter (MM): 10MM
Outside Diameter (MM): 22MM
Width (MM): 6MM
Dynamic Load Rating (KN): 2.7
Static Load Rating (KN): 1.27

SKF

MECHANICAL SEAL



Eagleburgmann Mechseal AD510 / Ad520

Pressure: p = vacuum (7 mbara) ... 5 bar (73 PSI)
Temperature: t = -30 °C ... +175 °C (-22 °F ... +347 °F)
Sliding velocity: vg = max. 1.0 m/s (3 ft/s)
Allowable gas consumption: 2 NI/h
"Seal face: PTFE, Carbon fiber and glass fiber reinforced Seat: Silicon carbide (Q1), Aluminium oxide (V)"

EagleBurgmann

PNEUMATIC

FESTO



Festo Pneumatic Cylinder 63mm Bore, 160mm Stroke, DSBC Series, Double Acting

ISO Standard 15552
Maximum Operating Pressure 12 bar
VDMA Standard 24562
Height 75 mm
Minimum Operating Temperature -20 °C
Stroke 160 mm
Weight 1.7 kg
Dimensions 353.1 x 75 x 75 mm
Model Number p 1383584

AirTAC



AirTAC Pneumatic Cylinder SC80X100 SC80X125 SC80X150 SC80X175S SC Series Standard Pneumatic Cylinder

Acting type: Double Acting
"Fluid: Air (to be filtered by 40µm filter element)"
Operating pressure:
0.10~1.0MPa(15~145psi)(1.0~10.0bar)
Proof pressure: 1.5MPa(215psi)(15bar)
Temperature: -20~80
Speed rang (mm/s): 30~800
Stroke tolerance? 0~250(0~+0.1) 251~1000(0~+1.4)
1001~1500(0~+1.8)

TOOLS



KTI INDONESIA
Zoom Your *Bussiness*



PRODUCT CATALOG



KTI INDONESIA
Zoom Your *Bussiness*

Star Safira Regency Cluster Nabilla B2/29
Kec. Suko Kab. Sidoarjo - Jawa Timur, 61258
Telp. +6231 8558 7417
www.karyateknologi.co.id | sales@karyateknologi.co.id



www.karyateknologi.co.id

AUTOMATION



ABB Energy Analysers QA/S4.64.1

- Unit : 1pc
- Product Type : QA/S4.64.1
- Product Depth/Length : 64.5 mm
- Product Height : 90 mm
- Product Width : 72 mm
- Compatible Bus Systems : Modbus
- Width in Number of Modular Spacings : 4
- Degree of Protection IP20Mounting Type : DIN-Rail
- Berat (Kg) : 0.1



ABB Logic Relays 1SVR440723R0300

- Model Number : 1SVR440723R0300
- Unit : 1pc
- Product Type : CL-LMR.C18AC2
- Berat (Kg) : 0.3
- Tanggal Produk Terdaftar : 7/3/2019
- Terakhir Diperbaharui : 2/27/2022

ABB



OMRON NX Series + NX1 + CPU Unit

- Model Number : NX102-1020
- Unit : 1pc
- Program Memory Capacity (MB) : 5
- Position Control : 4 axes (single axis)
- Unit Type : Database connection CPU unit
- Number of control axes : 2 axes
- M Code : 61729703
- Berat (Kg) : 0.1
- Tanggal Produk Terdaftar : 6/28/2022
- Terakhir Diperbaharui : 1/20/2023



OMRON Programmable Controller

- Model Number : CJ1WID232CHN
- Unit : 1pc
- Common Specifications : 16 points per common
- Current Consumption (A) : 0.09 (5V)
- External Connection : Fujitsu connector
- Occupied In/Out Points : Input/2CH
- Input Voltage (V) : DC 24
- Input Current (mA) : 4.1
- Number of Input Points : 32 points

OMRON



SIEMENS SCALANCE S615 LAN Router

- Model Number : 6GK5615-0AA00-2AA2
- Unit : 1pc
- Transfer Rate (Mbit/s) : 10, 100
- Supply Voltage/I/Rated Value : 10.8 V ... 28.8 V
- Power Loss/I/Rated Value : 4 W
- Consumed Current/I/Maximum : 0.2 A
- Product Component/I/Fusing at Power Supply Input : Yes
- Dimensions (WxHxD) (mm) : 35x147x127
- Net Weight (kg) : 0.4
- Product Function (VPN Connection) : IPsec, OpenVPN (as client for SINEMA RC)
- Type of Encryption Algorithms (VPN Connection) : AES-256, AES-192, AES-128, 3DES-168, DES-56
- Type of Auth. Procedure (VPN Connection) : Preshared key (PSK), X.509v3 certificates
- Type of Hashing Algorithms (VPN Connection) : MD5, SHA-1, SHA-256, SHA-384, SHA-512
- Type of Electrical Connection for Digital Input Signals : 2-pole terminal block
- Type of Electrical Connection for Digital Output Signals : 2-pole terminal block
- Berat (Kg) : 3.5



Electronic Module SIMATIC S7-1500

- Model Number : 6ES7515-2AM01-0AB0
- Unit : 1pc
- Packaging Dimensions : 15x15.40x4.60 mm
- Rated Voltage : 24 V DC
- Rated Current : 0.8 A
- Power Loss : 6.3 W
- Berat : 0.9 kg

SIEMENS

MEASUREMENT



Pressure Gauge FLK-700G08 1000 PSIG

- Model Number : FLK-700G08
- Unit : 1pc
- Range (psi) : -14 to 1000
- Range (bar) : -0.97 to 69
- Resolution (psi) : 0.
- 1Resolution (bar) : 0.001
- Accuracy (%) : ±0.05 FS (Positive pressure), ±0.1 FS (Vacuum)
- Burst Pressure (psi) : 4000
- Burst Pressure (bar) : 266
- Berat (Kg) : 0.5



750P07 Gauge Pressure Module 0-35 Bar, 4X Burst Rating

- Parameter Range : 0 to 500 psi (0 to 35 bar)
- Burst Rating : 4X
- Hi Side Media : 316 SS
- Lo Side Media : NA
- Reference Uncertainty : ±0.0175 %
- Total Uncertainty 1 year (15-35°C) : ± 0.035 %

FLUKE



Digital Multimeter 1011

- Tegangan DC : 600.0mV/6.000/60.00/600.0/600V
- Tegangan AC : 6.000/60.00/600.0/600V
- Uji Dioda Tegangan 2.8V, Uji Arus 0.4mA
- Kapasitansi : 40/400nF/4/40/400/4000µF
- Frekuensi : 10/100/1000Hz/10/100/1000kHz/10MHz
- Ukuran (L x W x D) : 161 x 82 x 50mm
- Berat : 280 g



AC/DC Clamp Meters 2033

- AC : A 40/300A ±1%rdg±4dgt [50/60Hz] (0 - 40A)
- DC : A 40/300A
- CONDUCTOR SIZE : Ø24mm max.
- FREQUENCY RESPONSE DC : 20Hz - 1kHz
- SAFETY STANDARD : IEC 61010-1 CAT III 300V
- POWER SOURCE : LR-44 (1.5V) x 2
- DIMENSIONS : 147(L) x 59(W) x 25(D)mm

KYORITSU

PUMP



Pompa Rendam (Pompa Celup) SP2A-18 Oil Meter

- Model Number : SP2A-18
- Power P1 (kW) : 1.130
- Motor Power (kW) : 0.75
- Thrust Capacity (lpm/m) : 33/69
- Max. Thrust (m) : 107
- Rated (HP/Phase) : 1/1
- Rated Flow (m³/h) : 2
- Rated Head (m) : 72
- Pump Outlet : 1.25
- Motor Diameter (inch) : 4
- Rated Voltage (V) : 1 x 230
- Rated Power - P2 (kW) : 0.75
- Berat (Kg) : 18



Pompa Dorong Set (Transfer Pump) CM PT 3-5 (CMB 3-46 PT)

- Model Number : CM PT 3-5
- Speed For Pump Data (rpm) : 2900
- Rated Voltage (V) : 1x220-240
- Mains Frequency (Hz) : 50
- Dimensions (cm) : 44x29x64
- Pump Outlet : 1
- Rated Speed (rpm) : 2730-2740
- Rated Power-P2 (kW) : 0.5
- Enclosure class (IEC 34-5) : Ip55
- Berat (Kg) : 21

GRUNDFOS



Submersible Pump DL Series 100 DLC 5, 5.5kW 1PC

- Diameter Sucion (mm) : 100
- Power (kW) : 5.5
- Frequency (Hz) : 50
- Type 4 Pole, air-Filled water light
- Type of Liquid Handle Sewage, Waste Water
- Synchronous Speed (min-1) : 1500
- Operation : Manual Type
- Berat (Kg) : 5



POMPA 100 DLC 57.5, 7.5kW 10 Hp

- Model : Ebara 100 DLC 57.5
- Catu daya : 380v/3p/50hz
- Daya : 7.5kw (10 hp)
- Kepala : 26,5-15,3 m
- Aliran : 24-108 m³/jam
- Tenggorokan knalpot : 100 mm

EBARA



Submersible Pump TOS100B43.7, 3.7kW

- Discharge Bore mm : 100
- Free Standing : 100B43.7
- Motor output : 3.7
- Phase : Three
- Speed (s.s) 50Hz/60Hz min-1 : 500/1800
- Starting method : D.O.L
- Impeller Passage 50Hz/60Hz mm : 81x53/81x47
- Cable length m : 6
- Cable Code : B(C)
- Free Standing : 602x690
- Guid Rail TOS : 760x700



Submersible Pump TOS100B43.7, 3.7kW

- Model : 100B42.2
- Discharge Size(in.) : 4
- Motor Output(HP) : 3
- Diameter(in.) : 24 1/4
- Height (in.) : 24 1/4
- Max Solid Diameter(in.) : 1.77
- Weight : 154lbs

TSURUMI PUMP

SST-0001394 - FLOWERVE SIHI Liquid Ring Vacuum Pump



- Brand : FLOWERVE Ex. GERMANY
- Type : LEMA 150 AZ AAE OA O CX
- Suction : 50 mm (= 2 Inch)
- Discharge : 40 mm (= 1 Inch)
- Speed : 1400 Rpm
- Material : Casing Cast Iron , Vanewheel Impeller Bronze,

FLOWERVE

VALVE



Fisher™ GX Control Valve and Actuator System

- Critical Service : Noise Abatement, Cavitation, Erosive, Low Flow, Corrosive, General Service
- Flow Characteristics : Equal Percentage, Linear, Special Characterization
- Material : Carbon Steel, Stainless, Duplex, Alloy
- Pressure Class : CL150, CL300, PN10/16, PN10/16/25/40, PN25/40
- Process Connection Type : Flanged
- Valve Size : NPS 1/2, NPS 3/4, NPS 1, NPS 1-1/2, NPS 2, NPS 3, NPS 4, NPS 6

FISHER



Kitz 150 Type Brass Gate Valve E Series 25A

- Model Number : E
- Material (Handle) : ZDC
- Material (Body) : CAC
- Material (bonnet) : C3771BE
- Dimension H (mm) : 122
- Dimension d (mm) : 70
- Interplanar dimension (mm) : 62
- Dimension L (mm) : 62

KITZ

GENERATOR



YANMAR YDG5001SE D Mesin Generator Silent

- Tipe : YDG5001SE Deluxe
- Mesin : 4 cycle, Berpendingin Udara, Diesel Vertical
- Frekuensi : 50 Hz
- Arus Keluaran : 4200 Watt
- Arus Keluaran Max : 4600 Watt
- Bahan Bakar : Solar Kapasitas
- Oli Mesin : 1.65 liter Kapasitas
- Bahan Bakar : 16 Liter
- Sistem Starter : Elektrik
- Berat : 200 kg
- Dimensi : 111 x 55 x 78 cm

YANMAR



Diesel Generator Less Than 75 dBA 880 kVA

- Fuel Type : Diesel
- Usage/Application : Commercial
- Genset Rating KVA : 880 KVA
- Noise Level : Less than 75 dBA
- Frequency : 50 Hz
- Phase : Three

Perkins