

# General Purpose

(Competitive Efficiency!)



- IE3 efficiency to IEC60034-30-1
- Also available in IE1 & IE2
- Top Mount T/Box
- Class F Insulation standard
- IP55 standard
- PTC (winding) from 160 frame and above
- WISE “Spike Resistant” Windings for use on VSD
- Multi mount to 132 frame (inclusive)
- Available in 2,4, and 6P
- Rated Power to 185kW, and
- Available for immediate order

# Industrial

(Latest WEG design for Induction Motors!)



- IE3 efficiency to IEC60034-30-1
- IE4 Efficiency also available
- Top Mount T/Box
- Class H Insulation (motor rated to 50 degree C ambient with 80K At temperature rise)
- IP56 protection
- PTC (windings) from 160 frame and above
- Shaft Grounding Brush from 315 frame and above
- WISE “Spike Resistant” Windings for use on VSD
- Full internal Tropicalization →
- Multi mount to 132 frame (inclusive)
- Available in 2,4 and 6P
- Rated Power to 185kW, and
- Available for immediate order



Contact Us :

PT. Sentral Laharindo Servis

Jl. Jemursari No.218-218A Surabaya,

Jawa Timur - 60292



+6231 - 847 9608



[enquiry@slssby.com](mailto:enquiry@slssby.com)